


SKiiP 37NAC12T4V1



MiniSKiiP® 3

3-phase Converter – Inverter (CI)


SKiiP 37NAC12T4V1

Features*

- Trench 4 IGBTs
- Robust and soft switching freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognized: File no. E63532

Remarks

- Max. case temperature limited to $T_C=125^{\circ}\text{C}$
- Product reliability results valid for $T_j \leq 150^{\circ}\text{C}$ (recommended $T_{j,op} = -40 \dots +150^{\circ}\text{C}$)
- Please refer to MiniSKiiP “Technical Explanations” and “Mounting Instructions” for further information




NAC

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Inverter - IGBT				
V_{CES}	$T_j = 25^{\circ}\text{C}$		1200	V
I_C	$\lambda_{paste}=0.8 \text{ W/(mK)}$	$T_s = 25^{\circ}\text{C}$	90	A
		$T_j = 175^{\circ}\text{C}$	73	A
I_C	$\lambda_{paste}=2.5 \text{ W/(mK)}$	$T_s = 25^{\circ}\text{C}$	106	A
		$T_j = 175^{\circ}\text{C}$	86	A
I_{Chom}			75	A
I_{CRM}			225	A
V_{GES}			-20 ... 20	V
t_{psc}	$V_{CC} = 800 \text{ V}$	$T_j = 150^{\circ}\text{C}$	10	μs
	$V_{GE} \leq 15 \text{ V}$			
	$V_{CES} \leq 1200 \text{ V}$			
T_j			-40 ... 175	$^{\circ}\text{C}$
Inverse - Diode				
V_{RRM}	$T_j = 25^{\circ}\text{C}$		1200	V
I_F	$\lambda_{paste}=0.8 \text{ W/(mK)}$	$T_s = 25^{\circ}\text{C}$	83	A
		$T_j = 175^{\circ}\text{C}$	66	A
I_F	$\lambda_{paste}=2.5 \text{ W/(mK)}$	$T_s = 25^{\circ}\text{C}$	95	A
		$T_j = 175^{\circ}\text{C}$	76	A
I_{FRM}			225	A
I_{FSM}	$t_p = 10 \text{ ms, sin } 180^{\circ}, T_j = 150^{\circ}\text{C}$		430	A
T_j			-40 ... 175	$^{\circ}\text{C}$
Rectifier - Diode				
V_{RRM}	$T_j = 25^{\circ}\text{C}$		1600	V
I_F	$\lambda_{paste}=0.8 \text{ W/(mK)}$	$T_s = 25^{\circ}\text{C}$	81	A
		$T_j = 150^{\circ}\text{C}$	60	A
I_F	$\lambda_{paste}=2.5 \text{ W/(mK)}$	$T_s = 25^{\circ}\text{C}$	92	A
		$T_j = 150^{\circ}\text{C}$	68	A
I_{FSM}	$t_p = 10 \text{ ms}$	$T_j = 25^{\circ}\text{C}$	700	A
		$T_j = 150^{\circ}\text{C}$	490	A
i^2t	$t_p = 10 \text{ ms}$	$T_j = 25^{\circ}\text{C}$	2450	A^2s
		$T_j = 150^{\circ}\text{C}$	1200	A^2s
T_j			-40 ... 150	$^{\circ}\text{C}$
Module				
$I_t(\text{RMS})$	$T_{terminal} = 80^{\circ}\text{C}, 20 \text{ A per spring}$		80	A
T_{stg}	module without TIM		-40 ... 125	$^{\circ}\text{C}$
V_{isol}	AC sinus 50 Hz, 1 min		2500	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverter - IGBT						
$V_{CE(sat)}$	$I_C = 75 \text{ A}$ $V_{GE} = 15 \text{ V}$ chiplevel	$T_j = 25^{\circ}\text{C}$	1.85	2.10		V
		$T_j = 150^{\circ}\text{C}$	2.25	2.45		V
V_{CE0}	chiplevel	$T_j = 25^{\circ}\text{C}$	0.80	0.90		V
		$T_j = 150^{\circ}\text{C}$	0.70	0.80		V
r_{CE}	$V_{GE} = 15 \text{ V}$ chiplevel	$T_j = 25^{\circ}\text{C}$	14	16		$\text{m}\Omega$
		$T_j = 150^{\circ}\text{C}$	21	22		$\text{m}\Omega$
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 3 \text{ mA}$		5	5.8	6.5	V
I_{CES}	$V_{GE} = 0 \text{ V}, V_{CE} = 1200 \text{ V}, T_j = 25^{\circ}\text{C}$				1	mA

SKiiP 37NAC12T4V1



MiniSKiiP® 3

3-phase Converter – Inverter (CI)

SKiiP 37NAC12T4V1


Features*

- Trench 4 IGBTs
- Robust and soft switching freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognized: File no. E63532

Remarks

- Max. case temperature limited to $T_C=125^{\circ}\text{C}$
- Product reliability results valid for $T_j \leq 150^{\circ}\text{C}$ (recommended $T_{j,op} = -40 \dots +150^{\circ}\text{C}$)
- Please refer to MiniSKiiP “Technical Explanations” and “Mounting Instructions” for further information

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
Inverter - IGBT					
C_{ies}	$V_{CE} = 25\text{ V}$	$f = 1\text{ MHz}$	4.40		nF
C_{oes}	$V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	0.29		nF
C_{res}		$f = 1\text{ MHz}$	0.24		nF
Q_G	$V_{GE} = -8\text{ V} \dots +15\text{ V}$		425		nC
R_{Gint}	$T_j = 25^{\circ}\text{C}$		10		Ω
$t_{d(on)}$	$V_{CC} = 600\text{ V}$	$T_j = 150^{\circ}\text{C}$	150		ns
t_r	$I_C = 75\text{ A}$	$T_j = 150^{\circ}\text{C}$	32		ns
E_{on}	$R_{G\ on} = 2\ \Omega$	$T_j = 150^{\circ}\text{C}$	9.7		mJ
$t_{d(off)}$	$R_{G\ off} = 2\ \Omega$	$T_j = 150^{\circ}\text{C}$	355		ns
t_f	$di/dt_{on} = 2400\text{ A}/\mu\text{s}$	$T_j = 150^{\circ}\text{C}$	60		ns
E_{off}	$V_{GE} = +15/-15\text{ V}$	$T_j = 150^{\circ}\text{C}$	6.8		mJ
$R_{th(j-s)}$	per IGBT, $\lambda_{paste}=0.8\text{ W}/(\text{mK})$		0.58		K/W
$R_{th(j-s)}$	per IGBT, $\lambda_{paste}=2.5\text{ W}/(\text{mK})$		0.44		K/W
Inverse - Diode					
$V_F = V_{EC}$	$I_F = 75\text{ A}$	$T_j = 25^{\circ}\text{C}$	2.17	2.49	V
	$V_{GE} = 0\text{ V}$	$T_j = 150^{\circ}\text{C}$	2.11	2.42	V
	chipelevel				
V_{F0}		$T_j = 25^{\circ}\text{C}$	1.30	1.50	V
	chipelevel	$T_j = 150^{\circ}\text{C}$	0.90	1.10	V
r_F		$T_j = 25^{\circ}\text{C}$	12	13	m Ω
	chipelevel	$T_j = 150^{\circ}\text{C}$	16	18	m Ω
I_{RRM}	$I_F = 75\text{ A}$	$T_j = 150^{\circ}\text{C}$	62		A
Q_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150^{\circ}\text{C}$	12.6		μC
	$V_{CC} = 600\text{ V}$				
E_{rr}	$di/dt_{off} = 1940\text{ A}/\mu\text{s}$	$T_j = 150^{\circ}\text{C}$	4.9		mJ
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W}/(\text{mK})$		0.75		K/W
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=2.5\text{ W}/(\text{mK})$		0.61		K/W
Rectifier - Diode					
$V_F = V_{EC}$	$I_F = 25\text{ A}$	$T_j = 25^{\circ}\text{C}$	1.00	1.21	V
	chipelevel	$T_j = 125^{\circ}\text{C}$	0.90	1.10	V
V_{F0}		$T_j = 25^{\circ}\text{C}$	0.88	0.98	V
	chipelevel	$T_j = 125^{\circ}\text{C}$	0.73	0.83	V
r_F		$T_j = 25^{\circ}\text{C}$	4.8	9.2	m Ω
	chipelevel	$T_j = 125^{\circ}\text{C}$	6.8	11	m Ω
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=0.8\text{ W}/(\text{mK})$		0.9		K/W
$R_{th(j-s)}$	per Diode, $\lambda_{paste}=2.5\text{ W}/(\text{mK})$		0.75		K/W
Module					
M_s	to heat sink	2		2.5	Nm
w			82		g
Temperature Sensor					
R_{100}	$T_r=100^{\circ}\text{C}$ ($R_{25}=1000\ \Omega$)		$1670 \pm 3\%$		Ω
$R_{(T)}$	$R_{(T)}=1000\ \Omega[1+A(T-25^{\circ}\text{C})+B(T-25^{\circ}\text{C})^2]$, $A = 7.635 \cdot 10^{-3}\text{ }^{\circ}\text{C}^{-1}$, $B = 1.731 \cdot 10^{-5}\text{ }^{\circ}\text{C}^{-2}$				



NAC




Fig. 1: Typ. output characteristic, inclusive R_{CC+EE}




Fig. 2: Typ. rated current vs. temperature $I_C = f(T_s)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic











Fig. 6: Typ. gate charge characteristic




SKiP 37NAC12T4V1

Pin out											
Pin	X	Y	Function	Pin	X	Y	Function	Pin	X	Y	Function
1	15,83	-25,30	g5	31	-16,05	-15,02		61	-39,33	25,30	
2	15,83	-6,40	E5	32	-16,05	-11,82	U	62	-40,23	-25,30	rect+
3	15,83	-3,20	W	33	-16,05	-8,62	U	63	-40,23	-22,10	rect+
4	15,83	0	W	34	-16,05	-5,42	E1	64	-40,23	-15,70	
5	15,83	3,20	W	35	-19,23	-25,30	g1	65	-40,23	-12,50	
6	15,83	6,40	W	36	-19,70	-15,02		66	-40,23	-9,30	DC+
7	15,83	15,70		37	-19,70	-11,82	U	67	-40,23	-6,10	DC+
8	15,83	18,90		38	-19,70	-8,62	U	68	-50,18	-25,30	L1
9	15,83	22,10	g6	39	-19,70	-5,42		69	-50,18	-22,10	L1
10	15,83	25,30	E6	40	-22,26	-1,00		70	-50,18	-18,90	
11	8,13	-25,30	T-	41	-22,26	2,20		71	-50,18	-15,70	
12	8,13	-22,10	T+	42	-22,68	22,10	DC-	72	-50,18	-9,50	L2
13	8,13	22,10		43	-22,68	25,30	DC-	73	-50,18	-6,30	L2
14	8,13	25,30	DC-	44	-25,91	-1,00		74	-50,18	6,30	rect-
15	1,83	-15,39		45	-25,91	2,20		75	-50,18	9,50	rect-
16	1,83	-12,19	E3	46	-29,18	8,74		76	-50,18	22,10	L3
17	1,83	-8,99	V	47	-29,18	11,94		77	-50,18	25,30	L3
18	1,83	-5,79	V	48	-32,83	8,74		78	-53,83	-25,30	L1
19	0,43	22,10	g4	49	-32,83	11,94		79	-53,83	-22,10	L1
20	0,43	25,30	E4	50	-35,68	22,10		80	-53,83	-18,90	
21	-1,08	-25,30	g3	51	-35,68	25,30		81	-53,83	-15,70	
22	-1,83	-15,39		52	-36,58	-25,30	rect+	82	-53,83	-9,50	L2
23	-1,83	-12,19		53	-36,58	-22,10	rect+	83	-53,83	-6,30	L2
24	-1,83	-8,99	V	54	-36,58	-15,70		84	-53,83	3,10	
25	-1,83	-5,79	V	55	-36,58	-12,50		85	-53,83	6,30	rect-
26	-5,83	3,95		56	-36,58	-9,30	DC+	86	-53,83	9,50	rect-
27	-7,28	22,10		57	-36,58	-6,10	DC+	87	-53,83	22,10	L3
28	-7,28	25,30	DC-	58	-39,33	15,70		88	-53,83	25,30	L3
29	-14,98	22,10	g2	59	-39,33	18,90					
30	-14,98	25,30	E2	60	-39,33	22,10					

all values in mm



Pinout and Dimensions



Pinout

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.