

SKM600GAR12T4



SEMITRANS® 3

Fast IGBT4 Modules

SKM600GAR12T4

Features*


- IGBT4 = 4th generation fast trench IGBT (Infineon)
- CAL4 = Soft switching 4th generation CAL-diode
- Insulated copper baseplate using DBC technology (Direct Bonded Copper)
- Increased power cycling capability
- With integrated gate resistor
- For higher switching frequencies up to 20kHz
- UL recognized, file no. E63532

Typical Applications

- Electronic welders at fsw up to 20 kHz
- DC/DC – converter
- Brake chopper
- Switched reluctance motor

Remarks

- Case temperature limited to $T_c = 125^\circ\text{C}$ max.
- Recommended $T_{op} = -40 \dots +150^\circ\text{C}$
- Product reliability results valid for $T_j = 150^\circ\text{C}$



GAR

Absolute Maximum Ratings			
Symbol	Conditions	Values	Unit
IGBT			
V_{CES}	$T_j = 25^\circ\text{C}$	1200	V
I_C	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	860
		$T_c = 80^\circ\text{C}$	702
I_{Cnom}		600	A
I_{CRM}		1800	A
V_{GES}		-20 ... 20	V
t_{psc}	$V_{CC} = 800\text{ V}$	$T_j = 150^\circ\text{C}$	10
	$V_{GE} \leq 15\text{ V}$		
	$V_{CES} \leq 1200\text{ V}$		μs
T_j		-40 ... 175	$^\circ\text{C}$
Inverse diode			
V_{RRM}	$T_j = 25^\circ\text{C}$	1200	V
I_F	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	623
		$T_c = 80^\circ\text{C}$	466
I_{Fnom}		500	A
I_{FRM}		1200	A
I_{FSM}	$t_p = 10\text{ ms, sin } 180^\circ, T_j = 25^\circ\text{C}$	2736	A
T_j		-40 ... 175	$^\circ\text{C}$
Freewheeling diode			
V_{RRM}	$T_j = 25^\circ\text{C}$	1200	V
I_F	$T_j = 175^\circ\text{C}$	$T_c = 25^\circ\text{C}$	707
		$T_c = 80^\circ\text{C}$	529
I_{Fnom}		600	A
I_{FRM}		1200	A
I_{FSM}	$t_p = 10\text{ ms, sin } 180^\circ, T_j = 25^\circ\text{C}$	3240	A
T_j		-40 ... 175	$^\circ\text{C}$
Module			
$I_{t(RMS)}$		500	A
T_{stg}	module without TIM	-40 ... 125	$^\circ\text{C}$
V_{isol}	AC sinus 50 Hz, $t = 1\text{ min}$	4000	V

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
IGBT					
$V_{CE(sat)}$	$I_C = 600\text{ A}$ $V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	1.80	2.05	V
		$T_j = 150^\circ\text{C}$	2.20	2.42	V
V_{CE0}	chipelevel	$T_j = 25^\circ\text{C}$	0.80	0.90	V
		$T_j = 150^\circ\text{C}$	0.70	0.80	V
r_{CE}	$V_{GE} = 15\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$	1.67	1.92	$\text{m}\Omega$
		$T_j = 150^\circ\text{C}$	2.5	2.7	$\text{m}\Omega$
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_C = 24\text{ mA}$	5	5.8	6.5	V
I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 1200\text{ V}, T_j = 25^\circ\text{C}$			5	mA
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$	$f = 1\text{ MHz}$	37.2		nF
C_{oes}		$f = 1\text{ MHz}$	2.32		nF
C_{res}		$f = 1\text{ MHz}$	2.04		nF
Q_G	$V_{GE} = -8\text{ V} \dots +15\text{ V}$		3400		nC
R_{Gint}	$T_j = 25^\circ\text{C}$		1.3		Ω



SEMITRANS® 3

Fast IGBT4 Modules

SKM600GAR12T4

Features*


- IGBT4 = 4th generation fast trench IGBT (Infineon)
- CAL4 = Soft switching 4th generation CAL-diode
- Insulated copper baseplate using DBC technology (Direct Bonded Copper)
- Increased power cycling capability
- With integrated gate resistor
- For higher switching frequencies up to 20kHz
- UL recognized, file no. E63532

Typical Applications

- Electronic welders at fsw up to 20 kHz
- DC/DC – converter
- Brake chopper
- Switched reluctance motor

Remarks

- Case temperature limited to $T_c = 125^\circ\text{C}$ max.
- Recommended $T_{op} = -40 \dots +150^\circ\text{C}$
- Product reliability results valid for $T_j = 150^\circ\text{C}$



GAR

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
$t_{d(on)}$	$V_{CC} = 600\text{ V}$	$T_j = 150^\circ\text{C}$		178		ns
t_r	$I_C = 600\text{ A}$	$T_j = 150^\circ\text{C}$		68		ns
E_{on}	$V_{GE} = +15/-15\text{ V}$	$T_j = 150^\circ\text{C}$		33		mJ
	$R_{G\ on} = 1.6\ \Omega$	$T_j = 150^\circ\text{C}$				
$t_{d(off)}$	$R_{G\ off} = 1\ \Omega$	$T_j = 150^\circ\text{C}$		523		ns
t_f	$di/dt_{on} = 8900\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		116		ns
	$di/dt_{off} = 4300\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$				
E_{off}	$dv/dt = 3550\text{ V}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		70		mJ
	$L_s = 24\text{ nH}$	$T_j = 150^\circ\text{C}$				
$R_{th(j-c)}$	per IGBT				0.049	K/W
$R_{th(c-s)}$	per IGBT ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)			0.032		K/W
$R_{th(c-s)}$	per IGBT, pre-applied phase change material			0.016		K/W
Inverse diode						
$V_F = V_{EC}$	$I_F = 600\text{ A}$	$T_j = 25^\circ\text{C}$		2.28	2.63	V
	$V_{GE} = 0\text{ V}$	$T_j = 150^\circ\text{C}$		2.28	2.61	V
	chipelevel	$T_j = 150^\circ\text{C}$				
V_{F0}	chipelevel	$T_j = 25^\circ\text{C}$		1.30	1.50	V
		$T_j = 150^\circ\text{C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25^\circ\text{C}$		1.64	1.88	m Ω
		$T_j = 150^\circ\text{C}$		2.3	2.5	m Ω
I_{RRM}	$I_F = 600\text{ A}$	$T_j = 150^\circ\text{C}$		566		A
Q_{rr}	$di/dt_{off} = 8700\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		99		μC
E_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150^\circ\text{C}$		40		mJ
	$V_{CC} = 600\text{ V}$	$T_j = 150^\circ\text{C}$				
$R_{th(j-c)}$	per diode				0.095	K/W
$R_{th(c-s)}$	per diode ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)			0.039		K/W
$R_{th(c-s)}$	per diode, pre-applied phase change material			0.028		K/W
Freewheeling diode						
$V_F = V_{EC}$	$I_F = 600\text{ A}$	$T_j = 25^\circ\text{C}$		2.14	2.46	V
	$V_{GE} = 0\text{ V}$	$T_j = 150^\circ\text{C}$		2.07	2.38	V
	chipelevel	$T_j = 150^\circ\text{C}$				
V_{F0}	chipelevel	$T_j = 25^\circ\text{C}$		1.30	1.50	V
		$T_j = 150^\circ\text{C}$		0.90	1.10	V
r_F	chipelevel	$T_j = 25^\circ\text{C}$		1.40	1.60	m Ω
		$T_j = 150^\circ\text{C}$		1.95	2.1	m Ω
I_{RRM}	$I_F = 600\text{ A}$	$T_j = 150^\circ\text{C}$		600		A
Q_{rr}	$di/dt_{off} = 9000\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		90		μC
E_{rr}	$V_{GE} = \pm 15\text{ V}$	$T_j = 150^\circ\text{C}$		39		mJ
	$V_{CC} = 600\text{ V}$	$T_j = 150^\circ\text{C}$				
$R_{th(j-c)}$	per diode				0.086	K/W
$R_{th(c-s)}$	per diode ($\lambda_{grease}=0.81\text{ W}/(\text{m}^2\text{K})$)			0.038		K/W
$R_{th(c-s)}$	per diode, pre-applied phase change material			0.024		K/W



SEMITRANS® 3

Fast IGBT4 Modules

SKM600GAR12T4

Features*

- IGBT4 = 4th generation fast trench IGBT (Infineon)
- CAL4 = Soft switching 4th generation CAL-diode
- Insulated copper baseplate using DBC technology (Direct Bonded Copper)
- Increased power cycling capability
- With integrated gate resistor
- For higher switching frequencies up to 20kHz
- UL recognized, file no. E63532


Typical Applications

- Electronic welders at fsw up to 20 kHz
- DC/DC – converter
- Brake chopper
- Switched reluctance motor

Remarks

- Case temperature limited to $T_c = 125^\circ\text{C}$ max.
- Recommended $T_{op} = -40 \dots +150^\circ\text{C}$
- Product reliability results valid for $T_j = 150^\circ\text{C}$

Characteristics				min.	typ.	max.	Unit
Symbol	Conditions						
Module							
L_{CE}				15			nH
$R_{CC'+EE'}$	measured per switch	$T_c = 25^\circ\text{C}$		0.55			m Ω
		$T_c = 125^\circ\text{C}$		0.85			m Ω
$R_{th(c-s)1}$	calculated without thermal coupling			0.0172			K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module ($\lambda_{grease}=0.81 \text{ W}/(\text{m}^2\text{K})$)			0.020			K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module, pre-applied phase change material			0.011			K/W
M_s	to heat sink M6			3		5	Nm
M_t							Nm
	to terminals M6			2.5		5	Nm
W						325	g



GAR




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl. R_{CC+EE}




Fig. 11: Typ. CAL diode peak reverse recovery current






Fig. 12: Typ. CAL diode peak reverse recovery charge

SKM600GAR12T4



SEMITRANS 3



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.