

# SKiM 300GD126DL



SKiM<sup>®</sup> 4

## IGBT Modules


### SKiM 300GD126DL

#### Features

- Trench gate IGBT with field stop layer
- Low inductance case
- Fast & soft inverse CAL diode
- Isolated by Al<sub>2</sub>O<sub>3</sub> DCB (Direct Copper Bonded) ceramic plate
- Pressure contact technology for thermal contacts
- Spring contact system to attach driver PCB to the control terminals
- Integrated temperature sensor

#### Typical Applications\*







- Switched mode power supplies
- Three phase inverters for AC motor speed control
- Switching (not for linear use)









GD




| Absolute Maximum Ratings |  | $T_{case} = 25^{\circ}\text{C}$ , unless otherwise specified |                    |
|--------------------------|--|--|--------------------|
| Symbol                   | Conditions   | Values   | Units              |
| <b>IGBT</b>              |  |  |                    |
| $V_{CES}$                |  | 1200   | V                  |
| $I_C$                    | $T_s = 25 (70) ^{\circ}\text{C}$                               | 270 (200)  | A                  |
| $I_{CRM}$                | $t_p = 1 \text{ ms}$   | 600  | A                  |
| $V_{GES}$                |  | $\pm 20$   | V                  |
| $T_j (T_{stg})$          |  | - 40 ... + 150 (125)   | $^{\circ}\text{C}$ |
| $T_{cop}$                | max. case operating temperature                                | 125  | $^{\circ}\text{C}$ |
| $V_{isol}$               | AC, 1 min.   | 2500   | V                  |
| <b>Inverse diode</b>     |  |  |                    |
| $I_F$                    | $T_s = 25 (70) ^{\circ}\text{C}$                               | 200 (145)  | A                  |
| $I_{FRM}$                | $t_p = 1 \text{ ms}$   | 400  | A                  |
| $I_{FSM}$                | $t_p = 10 \text{ ms}; \text{sin.}; T_j = 150 ^{\circ}\text{C}$ | 2200   | A                  |

| Characteristics                |  | $T_{case} = 25^{\circ}\text{C}$ , unless otherwise specified |             |            |               |
|--------------------------------|--|--|-------------|------------|---------------|
| Symbol                         | Conditions   | min.   | typ.        | max.       | Units         |
| <b>IGBT</b>                    |  |  |             |            |               |
| $V_{GE(th)}$                   | $V_{GE} = V_{CE}; I_C = 12 \text{ mA}$   | 5  | 5,8         | 6,5        | V             |
| $I_{CES}$                      | $V_{GE} = 0; V_{CE} = V_{CES}; T_j = 25 ^{\circ}\text{C}$  |  |             | 3,6        | mA            |
| $V_{CEO}$                      | $T_j = 25 (125) ^{\circ}\text{C}$  |  | 1 (0,9)     | 1,2 (1,1)  | V             |
| $r_{CE}$                       | $T_j = 25 (125) ^{\circ}\text{C}$  |  | 2,2 (3,5)   | 3 (4,3)    | m $\Omega$    |
| $V_{CEsat}$                    | $I_{Cnom} = 300 \text{ A}; V_{GE} = 15 \text{ V}; T_j = 25 (125) ^{\circ}\text{C}$ on chip level |  | 1,65 (1,95) | 2,1 (2,4)  | V             |
| $C_{ies}$                      | $V_{GE} = 0; V_{CE} = 25 \text{ V}; f = 1 \text{ MHz}$   |  | 22,5        |            | nF            |
| $C_{oes}$                      | $V_{GE} = 0; V_{CE} = 25 \text{ V}; f = 1 \text{ MHz}$   |  | 1,8         |            | nF            |
| $C_{res}$                      | $V_{GE} = 0; V_{CE} = 25 \text{ V}; f = 1 \text{ MHz}$   |  | 1,65        |            | nF            |
| $L_{CE}$                       |  |  | 10          | 15         | nH            |
| $R_{CC'+EE'}$                  | resistance, terminal-chip $T_c = 25 (125) ^{\circ}\text{C}$                                      |  | 1,35 (1,75) |            | m $\Omega$    |
| $t_{d(on)}$                    | $V_{CC} = 600 \text{ V}$   |  | 285         |            | ns            |
| $t_r$                          | $I_{Cnom} = 300 \text{ A}$   |  | 45          |            | ns            |
| $t_{d(off)}$                   | $R_{Gon} = R_{Goff} = 1 \Omega$  |  | 580         |            | ns            |
| $t_f$                          | $T_j = 125 ^{\circ}\text{C}$   |  | 95          |            | ns            |
| $E_{on} (E_{off})$             | $V_{GE} \pm 15 \text{ V}$  |  | 25 (36)     |            | mJ            |
| $E_{on} (E_{off})$             | with SKHI 6; $T_j = ^{\circ}\text{C}$<br>$V_{CC} = \text{V}; I_C = \text{A}$                     |  |             |            | mJ            |
| <b>Inverse diode</b>           |  |  |             |            |               |
| $V_F = V_{EC}$                 | $I_{Fnom} = 200 \text{ A}; V_{GE} = 0 \text{ V}; T_j = 25 (125) ^{\circ}\text{C}$                |  | 2 (1,8)     | 2,5 (2,3)  | V             |
| $V_{TO}$                       | $T_j = 25 (125) ^{\circ}\text{C}$  |  | 1,1 (0,85)  | 1,45 (1,2) | V             |
| $r_T$                          | $T_j = 25 (125) ^{\circ}\text{C}$  |  | 4,5 (4,8)   | 5,3 (5,5)  | m $\Omega$    |
| $I_{RRM}$                      | $I_F = 300 \text{ A}; T_j = 125 ^{\circ}\text{C}$  |  | 450         |            | A             |
| $Q_{rr}$                       | $V_{GE} = 0 \text{ V}; di/dt = 11000 \text{ A}/\mu\text{s}$                                      |  | 47          |            | $\mu\text{C}$ |
| $E_{rr}$                       | $R_{Gon} = R_{Goff} = 1 \Omega$  |  | 22          |            | mJ            |
| <b>Thermal characteristics</b> |  |  |             |            |               |
| $R_{th(j-s)}$                  | per IGBT   |  |             | 0,2        | K/W           |
| $R_{th(j-s)}$                  | per FWD  |  |             | 0,285      | K/W           |
| <b>Temperature Sensor</b>      |  |  |             |            |               |
| $R_{TS}$                       | $T = 25 (100) ^{\circ}\text{C}$  |  | 1 (1,67)    |            | k $\Omega$    |
| tolerance                      | $T = 25 (100) ^{\circ}\text{C}$  |  | 3 (2)       |            | %             |
| <b>Mechanical data</b>         |  |  |             |            |               |
| $M_1$                          | to heatsink (M5)   | 2  |             | 3          | Nm            |
| $M_2$                          | for terminals (M6)   | 4  |             | 5          | Nm            |
| w                              |  |  |             | 310        | g             |





# SKiM 300GD126DL



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

## \*IMPORTANT INFORMATION AND WARNINGS

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.